Now with Higher Lift Capacity

New
75 HP 55 kW 4WD
Model 5075 E
with **Inline FIP**
and
PowrReverser™

Do Kadam Aage...

Forward - Reverse tractor without operating clutch and gear

Saves time, increases productivity!

John Deere Promise
5 YEARS WARRANTY*
— TECHNOLOGY LEADERSHIP —

*Conditions apply.

Hood Lock

12 Forward GEAR SPEED 12 Reverse

Wide Range of Speed

5 Years/ 5000 hrs. Warranty*

On Wet Clutch

Electro-Hydraulic Wet Clutch

Zindagi ka Best Decision!™

JOHN DEERE

TECHNICAL SPECIFICATIONS

ENGINE

Type	:	75 HP (55 kW), 2400 RPM, 3 Cylinders, Direct injection, Turbo charged, Inline FIP, Coolant cooled with overflow reservoir
Air filter	:	Dry type, Dual element

TRANSMISSION

Clutch	:	Dual, Wet Clutch Technology, Suspended type pedals, Electro-Hydraulic Operation
Gear box	:	12 Forward + 12 Reverse Top Shaft Synchromesh (TSS)
Speeds	:	Forward 1.7 - 35.2 kmph Reverse 1.8 - 38.3 Kmph
Forward & Reverse	:	Through lever on steering column

BRAKES

	:	Self adjusting and self equalising, hydraulically actuated, Oil immersed disc brakes

HYDRAULICS

Maximum Lifting capacity	:	2000 kgf
3 point linkage	:	Category - II Automatic depth & draft control (ADDC)

STEERING

Type	:	Power

POWER TAKE OFF

Type	:	Electro-Hydraulic Wet Clutch Dual, Independent, 6 Splines
Standard	:	540 @ 2376 ERPM
Economy	:	540 @ 1705 ERPM

WHEELS AND TYRES

Front	:	12.4 x 24 (0.31 x 0.61 m), 8 PR
Rear	:	18.4 x 30 (0.47 x 0.76 m), 12 PR

FUEL TANK

Capacity	:	Rear mounted, 68 L

ELECTRICAL SYSTEM

	:	85 Ah, 12 V battery, 43 Amp. Alternator, 12 V, 2.5 kW Starter motor
Instrument cluster	:	LCD display (Hour meter, Tractor speed and PTO RPM monitor)

WEIGHT AND DIMENSIONS

Total weight	:	2600 kg
Wheel base	:	2050 mm
Overall length	:	3630 mm
Overall width	:	1850 mm

ADDITIONAL FEATURES

- Finger-Touch Electro-Hydraulic Forward Reverse Lever with Neutral
- Maintenance-free Wet Clutch Technology
- Heavy Duty Front and Rear Axle
- Car type Engine On/Off
- ROPS - Roll over protection structure

5075 E also available in base model without *PowrReverser™*

New 75 HP 55 kW 4WD

Model 5075 E

with Inline FIP

and

PowrReverser™

Automatic hood opening
Single piece hood opening with gas struts

Finger guard
Enhanced safety

Side bar & steps with mat
Climbing up and down the tractor is now easier

Operator Presence Switch
Tractor will not move if there is no operator on seat

Electro-Hydraulic Operated PTO Switch

High torque reserve
More productivity

5075 E 4WD PR 01 0120 ENG

John Deere Genuine Parts

I Economical I Reliable I
I Easily available I

John Deere India Private Limited
3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar,
Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.

- Tractors • Implements
- Harvesters • Finance

JOHN DEERE

Please note: Improvement in the product is a continuous process. Hence the information given in this brochure is subject to change without prior notice. Accessories shown are not the part of standard equipment.