Now with Higher Lift Capacity

New

39 HP

Model 5039 D

John Deere 5D series

Milega Ummeed se Zyaada!

Productivity Plus

Fuel Efficiency Plus

Torque Plus

Value+++

Also available with JDLink™

Now warranty on tractor 2+1 Years 2000 + 1000 hours*

*Conditions apply.

Power Steering

Mobile Charging Point with Holder

Hood Lock

Planetary Gear with Straight Axle

Zindagi ka Best Decision!™

JOHN DEERE

Technical Specifications

ENGINE

Type	:	John Deere 3029D, 39 HP, 2100 RPM, 3 Cylinders, Coolant cooled with overflow reservoir, Naturally aspirated
Air filter	:	Dry type, Dual element

TRANSMISSION

Clutch	:	Single / Dual
Gear box	:	8 Forward + 4 Reverse, Collarshift
Speeds	:	Forward 3.13 - 34.18 kmph Reverse 4.10 - 14.84 kmph

BRAKES

	:	Oil immersed disc brakes

HYDRAULICS

Maximum Lifting capacity	:	1600 kgf
3 point linkage	:	Category - II Automatic depth and draft control

STEERING

Type	:	Power

POWER TAKE OFF

Type	:	Independent, 6 Splines
Standard	:	540 @ 2100 ERPM
Economy	:	540 @ 1600 ERPM (Optional, available along with standard PTO)

WHEELS AND TYRES

Front	:	6.0 X 16, 8 PR
Rear	:	12.4 X 28, 12 PR (Optional) 13.6 X 28, 12 PR

FUEL TANK

Capacity	:	60 L

ELECTRICAL SYSTEM

	:	88 Ah, 12 V battery 40 Amp. alternator 12 V, 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight	:	1760 kg
Wheel base	:	1970 mm
Overall length	:	3400 mm
Overall width	:	1780 mm
Ground clearance	:	0390 mm
Turning radius with brakes	:	2900mm

ACCESSORIES*

- Ballast weights • Canopy • Canopy holder
- Draw bar • Tow hook • Wagon hitch

FACTORY FITTED OPTIONS

- JDLink™ (Alerts, Monitoring and Tracking System)
- Roll over protection system (ROPS) with deluxe seat and seat belt

- Adjustable front axle
- Mechanical quick raise and lower (MQRL)
- Dual PTO

FEATURES

- Collarshift type gear box • Finger guard • PTO NSS
- Underhood exhaust muffler • Water separator
- Digital Hour Meter

Note : All the options / features may not be available in a single variant.

Puddling special model is also available

New

39 HP

Model 5039 D

Modern, technologically advanced, powerful John Deere 3029D engine

- **Wet liner**

  Long life and less maintenance

- **High torque reserve**

  Ideal for heavy load applications

- **High torque across the operating speed range**

Dry Type Air Filter

Oil Jet for Piston Cooling

Radiator with Overflow Reservoir

Top Shaft Lubrication

5039 D 00 1017 ENG WEB

John Deere Genuine Parts

| Economical | Reliable |
| Easily available |

For more information, please contact our authorised dealer or nearest area office.

John Deere India Private Limited
3rd floor, Tower-15, Cybercity, Magarpatta City,
Hadapsar, Pune - 411013. Maharashtra.

Please note: Improvement in the product is a continuous process.
Hence the information given in this brochure is subject to change without prior notice.
Accessories shown are not the part of standard equipment.

JOHN DEERE

• Tractors • Farm Equipment • Finance

www.JohnDeere.co.in