







Single piece hood with lock



International Looks



Also available with





Type

2100 RPM, 3 Cylinders, Coolant cooled with overflow

reservoir, Naturally aspirated

Air filter : Dry type, Dual element

TRANSMISSION

Clutch : Single / Dual

Gear box : 8 Forward + 4 Reverse, Collarshift Speeds : Forward 2.97 - 32.44 kmph Reverse 3.89 - 14.09 kmph

BRAKES

: Oil immersed disc brakes

HYDRAULICS

Maximum Lifting capacity: 1600 kgf 3 point linkage: Category - II

Automatic depth and draft control

(ADDC)

STEERING

Type : Power

POWER TAKE OFF

Type : Independent, 6 Splines Standard : 540 @ 2100 ERPM Economy : 540 @ 1600 ERPM

WHEELS AND TYRES

Front : 6.0 x 16 (0.15 x 0.41 m), 8 PR

(Optional) 7.5 x 16 (0.19 x 0.41 m), 8 PR

Rear : 14.9 x 28 (0.38 x 0.71 m), 12 PR (Optional) 16.9 x 28 (0.43 x 0.71 m), 12 PR **FUEL TANK**

Capacity : 60 L

ELECTRICAL SYSTEM

: 88 Ah, 12 V battery, 40 Amp. alternator,

12 V, 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight : 1870 kg
Wheel base : 1970 mm
Overall length : 3430 mm
Overall width : 1830 mm
Ground clearance : 0430 mm
Turning radius with brakes : 2900 mm

ACCESSORIES*

• Ballast weights • Canopy • Canopy holder

• Draw bar • Tow hook • Wagon hitch

FACTORY FITTED OPTIONS

• Jollink (Alerts, Monitoring and Tracking System)

• Reverse PTO • Dual PTO

 Roll over protection structure (ROPS) with deluxe seat and seat belt

Adjustable front axle

Mechanical guick raise and lower (MQRL)

Selective control valve (SCV)

FEATURES

• Collarshift type gear box • PTO NSS • Water separator

• Digital hour meter • Mobile charging point with holder

• Planetary gear with straight axle • Hydraulic auxiliary pipe

• Finger quard • Underhood exhaust muffler

Note: All the options / features may not be available in a single variant.

4WD model is also available

New **5050 D**

Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner
 Long life and less maintenance

High torque reserve Ideal for heavy load applications

High torque across the operating speed range

Rear oiled axle with metal face seal



Dry Type Air Filter



Oil Jet for Piston Cooling



Plus

Torque

Radiator with Overflow Reservoir



Value###

Top Shaft Lubrication

John Deere Genuine Parts


I Economical I Reliable I Easily available I



4WD model is also available

John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in











Harvesters • Finance

