







Oil Immeresed Disc Brakes



Hood Lock



Mobile Charging point with Holder



Planetary Gear with Straight Axle





## **Technical Specifications**

**ENGINE** 

: John Deere 3029D, 36 HP, Type

2100 RPM, 3 Cylinders,

Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

TRANSMISSION

Clutch : Sinale

8 Forward + 4 Reverse, Collarshift Gear box

Speeds : Forward 3.13 - 34.18 kmph

Reverse 4.10 - 14.84 kmph

**BRAKES** 

: Oil immersed disc brakes

**HYDRAULICS** 

Maximum Lifting capacity: 1600 kgf 3 point linkage Category - II

Automatic depth and draft control

**STEERING** 

Type : Power

**POWER TAKE OFF** 

: Independent, 6 Splines Type Standard : 540 @ 2100 ERPM

WHEELS AND TYRES

Front : 6.0 X 16.8 PR Rear : 12.4 X 28, 12 PR

13.6 X 28, 12 PR (Optional)

**FUEL TANK** 

Capacity : 60 L

**ELECTRICAL SYSTEM** 

: 88 Ah, 12 V battery 40 Amp. alternator

12 V. 2.5 kW Starter motor

**DIMENSIONS AND WEIGHT** 

: 1760 kg Total weight Wheel base : 1970 mm : 3400 mm Overall length Overall width : 1780 mm : 0390 mm Ground clearance Turning radius with brakes : 2900 mm

**ACCESSORIES\*** 

• Ballast weights • Canopy • Canopy holder

• Draw bar • Tow hook • Wagon hitch

• Journal (Alerts, Monitoring and Tracking System)

**FACTORY FITTED OPTIONS** 

 Roll over protection system (ROPS) with deluxe seat and seat belt



## **FEATURES**

- Collarshift gear box Finger guard PTO NSS
- Underhood exhaust muffler Water separator
- Digital Hour Meter

Note: All the options / features may not be available in a single variant.



## Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner

Long life and less maintenance

High torque reserve

Ideal for heavy load applications

High torque across the operating speed range

Multi-Utility Tractor



## John Deere **Genuine Parts**

I Economical I Reliable I Easily available I







• Tractors • Farm Equipment • Finance