



More performance, More life. Less maintenance, Useful for all farming applications



Power steering



Single piece hood with lock





Technical Specifications

ENGINE

Type : John Deere 3029D, 44 HP (32.8 kW),

2100 RPM, 3 Cylinders, Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

TRANSMISSION

Clutch : Single / Dual

Gear box : 8 Forward + 4 Reverse, Collarshift Speeds : Forward 2.83 - 30.92 kmph

Reverse 3.71 - 13.43 kmph

BRAKES

: Oil immersed disc brakes

HYDRAULICS

Maximum Lifting

capacity : 1600 kgf 3 point linkage : Category - II

Automatic depth and draft control

(ADDC)

STEERING

Type : Power

POWER TAKE OFF

Type : Independent, 6 Splines Standard : 540 @ 2100 ERPM Economy : 540 @ 1600 ERPM

(Optional, available along with standard PTO)

WHEELS AND TYRES

Front : 6.0 X 16 (0.15 X 0.41 m), 8 PR Rear : 13.6 X 28 (0.34 X 0.71 m), 12 PR **FUEL TANK**

Capacity : 60 L

ELECTRICAL SYSTEM

: 88 Ah, 12 V battery, 40 Amp. alternator 12 V. 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight : 1810 kg
Wheel base : 1970 mm
Overall length : 3410 mm
Overall width : 1810 mm
Ground clearance : 0415 mm
Turning radius with brakes : 2900mm

ACCESSORIES*

• Ballast weights • Canopy • Canopy holder

• Draw bar • Tow hook • Wagon hitch

FACTORY FITTED OPTIONS

• JDLink™ (Alerts, Monitoring and Tracking System)

Dual PTO • Reverse PTO

 Roll over protection structure (ROPS) with deluxe seat and seat belt

Adjustable front axle

Mechanical quick raise and lower (MQRL)

FEATURES

• Collarshift type gear box • PTO NSS • Water separator

• Digital Hour Meter • Mobile Charging Point with Holder

• Underhood exhaust muffler • Hydraulic auxiliary pipe

• Planetary Gear with Straight Axle • Finger Guard

Note: All the options / features may not be available in a single variant.



Modern, technologically advanced, powerful John Deere 3029D engine

- Wet linerLong life and less maintenance
- High torque reserve Ideal for heavy load applications
- High torque across the operating speed range
- Rear oiled axle with metal face seal



Dry Type Air Filter



Oil Jet for Piston Cooling



Radiator with Overflow Reservoir



Top Shaft Lubrication

John Deere Genuine Parts

I Economical I Reliable I Easily available I




John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.







• Harvesters • Finance

