With Higher Lift Capacity

Ploughing or pulling, 5210 has the edge !

50 HP 37.3 KW
The Powerful Hero
5210

*Conditons apply.

Power Brakes
Self adjusting, self equalising, hydraulically actuated, oil immersed disc brakes

High torque reserve
Ideal for heavy load applications

Multipurpose Heavy Duty Tractor

Zindagi ka Best Decision!™

JOHN DEERE

50 HP 37.3 kW
The Powerful Hero
5210

Power Steering
Work hard. Drive smooth

Oil Jet for Piston Cooling

John Deere Powerful engine
Save more Fuel

Dry type air filter

Planetary Gear with Straight Axle
Low noise, less vibration, highly durable

Single piece hood opening with gas struts
The daily inspection and routine maintenance now made easy

Top Shaft Lubrication

Hood Lock
Totally Secure

Mobile Charging Point with Holder
Stay connected anytime

John Deere Genuine Parts

I Economical I Reliable I Easily available I

TECHNICAL SPECIFICATIONS

ENGINE

Type	:	50 HP (37.3 kW), 2400 RPM, 3 Cylinders, Direct Injection, Turbo Charged, Inline FIP, Coolant cooled with overflow reservoir
Air filter	:	Dry type, Dual element

TRANSMISSION

Clutch	:	Dual
Gear box	:	9 Forward + 3 Reverse, Collarshift
Speeds	:	Forward 2.1 - 30.1 kmph Reverse 3.6 - 23.3 kmph

BRAKES

	:	Self adjusting and self equalising, Hydraulically actuated, Oil Immersed Disc Brakes

HYDRAULICS

Maximum Lifting capacity	:	2000 kgf
3 point linkage	:	Category - II Automatic depth and draft control (ADDC)

STEERING

Type	:	Power

POWER TAKE OFF

Type	:	Independent, 6 Splines
RPM	:	540 @ 2376 ERPM

WHEELS AND TYRES

Standard	:	Front - 6 X 16 (0.15 x 0.41m), 8 PR Rear- 14.9 X 28 (0.38 x 0.71 m),12 PR
Optional	:	Front - 7.5 X 16 (0.19 x 0.41 m), 8 PR/ 6.5 x 20 (0.17 x 0.51 m) Rear - 16.9 X 28 (0.43 x 0.71), 12 PR

FUEL TANK

Capacity	:	68 L

ELECTRICAL SYSTEM

	:	88 Ah, 12 V battery, 40 Amp. alternator, 12 V, 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight	:	2105 kg
Wheel base	:	2050 mm
Overall length	:	3540 mm
Overall width	:	1820 mm
Ground clearance	:	0440 mm
Turning radius with brakes	:	3181 mm

ACCESSORIES*

• Ballast weights • Canopy • Tow hook • Canopy holder
• Draw bar • Wagon hitch

ADDITIONAL FEATURES

- Selective Control Valve (SCV)
- Adjustable Front Axle
- Heavy Duty Front Axle
- Reverse PTO (Standard + Reverse)
- Dual PTO (Standard + Economy)

Note: 5 years warranty consist of 2 years / 2000 hours of standard warranty and extended warranty of 3 years / 3000 hours.

5210 D 00 0719 ENG

John Deere India Private Limited
3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar,
Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.

• **Tractors** • **Implements**
• **Harvesters** • **Finance**

JOHN DEERE

Please note: Improvement in the product is a continuous process. Hence the information given in this brochure is subject to change without prior notice. Accessories shown are not the part of standard equipment.