TECHNICAL SPECIFICATION

		2WD	4WD
ENGINE		50 HP (36.5 kW), 2100 RPM, 3 cylinder, Direct injection, Turbo charged, Inline FIP, coolant cooled with over flow reservoir	
AIR FILTER		Dry type, dual element	
TRANSMISSION	Clutch	Dual	
	Gear Box	12 Forward + 4 Reverse, Collarshift, TSS	
	Speeds	Forward 1.9 - 31.5 kmph Reverse 3.4 - 22.1 kmph	
BRAKES		Self Adjusting, Self Equalising, Hydraulically Actuated, Oil immersed disk brakes	
HYDRAULICS	Maximum Lifting capacity	2000 kgf	
	3 Point linkage	Category II, Automatic depth & draft control (ADDC)	
STEERING		Power Steering	
POWER TAKE OFF	Туре	Independent , 6 splines	
	RPM	Dual PTO Standard : 540 @ 2100 ERPM Economy : 540 @ 1600 ERPM	
FUEL TANK CAPACITY		68 L	
WHEELS AND TYRES	Front	6.5 x 20 (0.17 x 0.51 m), 8 PR 7.5 x 16 (0.19 x 0.41 m), 8 PR (Optional)	9.5 x 24 (0.24 x 0.61 m), 8 PR
	Rear	16.9 x 28 (0.43 x 0.71 m), 12 PR 14.9 x 28 (0.38 x 0.71 m), 12 PR (Optional)	16.9 x 28 (0.43 x 0.71 m), 12 PR
ELECTRICAL SYSTEM		88 Ah, 12 V battery, 40 Amp. Alternator, 2.5 kW starter motor	
DIMENSIONS AND WEIGHT	Total weight Wheel base Overall length Overall width Turning radius with brakes	2110 kg 2050 mm 3535 mm 1850 mm 3150 mm	2410 kg 2050 mm 3585 mm 1875 mm
OPTIONAL ACCESSORIES		Ballast Weight • Canopy • Canopy Holder • Draw Bar • Wagon Hitch	



FACTORY FITTED OPTIONS

- Adjustable front axle
- Heavy duty front axle
- Reverse PTO (Std + Reverse)
- Dual PTO (Std + Economy)
- EQRL system
- Synchromesh Transmission (TSS)
- Selective Control Valve (SCV)
- Roll over protection structure (ROPS) with deluxe seat and seat belt

ADDITIONAL FEATURES

- Single piece hood with gas strut mechanism
- Side bar, exhaust muffler guard & finger guard
- Water bottle holder
- Seat with arm rest (Optional)
- Suspended pedal

Note: 5 years warranty consist of 2 years / 2000 hours of standard warranty and extended warranty of 3 years / 3000 hours.

Note: All the options / features may not be available in a single variant.

John Deere **Genuine Parts**

I Easily available I




John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in









• Harvesters • Finance









Strength. Ease. Success.

We have always known your ambition for something extra in life... extra success, extra prosperity, extra happiness! This desire for extra reflects in the choice for your own tractor as well! With John Deere Tractor, you choose a path of profit and progress for life! So presenting exclusively for you the new John Deere **5210 GearPro** with extra range and extra power!

At John Deere, our focus is always to understand your needs and better our offerings with advanced technology to suit them. So we bring you the all powerful **5210 GearPro** for your regular farming activities as well as specialised loading, dozing and leveling. We are sure that it will prove to be your best choice!

The new **5210 GearPro** has many amazing features, including –

- 4 Gear range more gear options for more activities
- **High 38% back up torque** no need to change gears often
- More lifting capacity strength to lift weight upto 2000 kgs
- 4 Wheel drive less tyre slippage, more producivity

So give your dreams the strength to fly with the new **5210 GearPro** with Xtra range, Xtra power!





4 Gear Range More gear options for more activities




High Torque reserve ~ 38%Suitable for activities that require more pulling power or load bearing



More Lifting Capacity
Strength to lift weight
up to 2000 kilograms



EQRLEQRL switch eases lifting,
joining and use of implement



Sway BarEase in adjusting or joining implements



Planetary Gear with Straight axle Low noise, less vibration, highly durable







Oil immersed disc brakes Secure, durable, no need to change gears often



Mobile Charging Point with Holder Stay connected anytime



Hood Lock Totally secure



John Deere 3029H engine with Inline FIP Powerful and fuel efficient



Power SteeringWork hard. Drive smooth

