

Now with
Higher Lift Capacity

New
60 HP 44.7 kW **4WD**
Model 5060 E
with
PowerReverser™

Do Kadam Aage...



Forward - Reverse tractor
without operating clutch and gear



Saves time,
increases productivity!



*Conditions apply.



Hood Lock



Wide Range of Speed



On Wet Clutch



Electro-Hydraulic Wet Clutch

*Zindagi ka
Best Decision!™*



JOHN DEERE

TECHNICAL SPECIFICATIONS

ENGINE

Type	: 60 HP (44.7 kW), 2400 RPM, 3 Cylinders, Direct injection, Turbo charged, Rotary FIP, Liquid cooled with over flow reservoir
Air filter	: Dry type, Dual element

TRANSMISSION

Clutch	: Dual, Wet Clutch Technology, Electro-Hydraulic Operation,
Gear box	: 12 Forward + 12 Reverse Top Shaft Synchromesh (TSS)
Speeds	: Forward 1.6 - 32.5 kmph Reverse 1.7 - 35.5 Kmph
Forward & Reverse	: Through lever on steering column

BRAKES

	: Self adjusting and self equalising, hydraulically actuated, Oil immersed disc brakes
--	--

HYDRAULICS

Maximum Lifting capacity	: 2000 kgf
3 point linkage	: Category - II Single SCV Automatic depth and draft control (ADCC)

STEERING

Type	: Power
------	---------

POWER TAKE OFF

Type	: Electro-Hydraulic Wet Clutch Dual, Independent, 6 Splines
Standard	: 540 @ 2376 ERPM
Economy	: 540 @ 1705 ERPM

WHEELS AND TYRES

Front	: 9.5 x 24 (0.24 x 0.61 m), 8 PR
Rear	: 16.9 x 28 (0.43 x 0.71 m), 12 PR

FUEL TANK

Capacity	: 68 L
----------	--------

ELECTRICAL SYSTEM

	: 85 Ah, 12 V battery, 43 Amp. Alternator, 12 V, 2.5 kW Starter motor
Instrument cluster	: LCD display (Hour meter, Tractor speed and PTO RPM monitor)

WEIGHT AND DIMENSIONS

Total weight	: 2370 kg
Wheel base	: 2050 mm
Overall length	: 3580 mm
Overall width	: 1875 mm

ADDITIONAL FEATURES

- Finger-Touch Electro-Hydraulic Forward Reverse Lever with Neutral
- Maintenance-free Wet Clutch Technology
- Heavy Duty Front and Rear Axle
- Car type Engine On/Off

FACTORY FITTED OPTIONS

- Roll over protection system (ROPS) with deluxe seat and seat belt



5060 E also available in base model without PowerReverser™

New 60 HP ^{44.7 kW} 4WD Model 5060 E with PowerReverser™



Automatic hood opening
Single piece hood opening
with gas struts



Finger guard
Enhanced safety



Side bar & steps with mat
Climbing up and down the
tractor is now easier



Operator Presence Switch
Tractor will not move
if there is no operator on seat



**Electro-Hydraulic
Operated
PTO Switch**



**High torque
reserve**
More productivity

John Deere Genuine Parts

| Economical | Reliable |
| Easily available |



John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar,
Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.



- Tractors • Implements
- Harvesters • Finance

