# **TECHNICAL SPECIFICATION**

|                          |   |   | 4WD   |
|--------------------------|---|---|---|
| ENGINE                   |   | John Deere 3029H, 2100 EPRM, 57 HP, 3 cylinder, Turbo charged<br>HPCR fuel injection system   |   |
| AIR FILTER               |   | Dry type, dual element  |   |
|                          | Clutch  | Du  | ial   |
| TDANICANICCIONI          | Gear Box  | 12 Forward + 4 Reverse speed, 12F+12R (PR speed), 9F+3R with additional creeper speed   |   |
| TRANSMISSION             | Speeds  | Forward - 0.35 to 32.6 kmph (Creeper), 2.8 to 32.6 kmph (12x4 GearPRO), 1.4 to 31.3 kmph (PR) Reverse - 0.61 to 20 kmph (Creeper), 3.5 to 20 kmph (12x4 GearPRO), 1.6 to 20 kmph (PR) |   |
| BRAKES                   |   | Hydraulic oil immersed disk brakes  |   |
| IIVPPAHILICS N           | laximum Lifting Capacity  | 2000 kgf (2500 kgf optional)  |   |
| HYDRAULICS               | 3 Point Linkage   | Category II, Automatic depth & draft control (ADDC)   |   |
| STEERING                 |   | Power Steering , Tilt steering <sup>f</sup> : tiltable up to 25° with lock latch  |   |
| POWER                    | Туре  | Independent , 6 splines   |   |
| TAKE OFF                 | RPM   | Standard : 540 @ 2100 ERPM<br>Economy : 540 @ 1600 ERPM<br>Reverse : 516 @2100 RPM  |   |
| FUEL TANK CAPACITY       |   | 71 L  |   |
| WHEELS<br>AND TYRES      | Front   | 7.5X16 (0.19 x 0.41 m), 8 PR<br>6.5 x 20 (0.17 x 0.51 m), 8 PR  | 9.5 x 24 (0.24 x 0.61 m), 8 PR                      |
| AND THES                 | Rear  | 16.9 x 30 (0.43 x 0.76 m), 12 PR  | 16.9 x 30 (0.43 x 0.76 m), 12 PR                    |
| ELECTRICAL SYSTEM        |   | 85 Ah, 12 V Battery, Cold charging Amp - 800 CCA, 60 Amp, Alternator12V, 2,5 Kv Starter Motor   |   |
| DIMENSIONS<br>AND WEIGHT | Total Weight<br>Wheel Base<br>Overall Length<br>Overall Width<br>Ground Clearance | 2320 kg<br>2050 mm<br>3678 mm<br>2243 mm<br>0520 mm   | 2600 kg<br>2050 mm<br>3678 mm<br>2243 mm<br>0425 mm |
| Tu                       | rning Radius with Brakes  | 3181 mm   | 3181 mm   |
| OPTIONAL ACCESSORIES     |   | • Ballast Weight • Canopy • Canopy Holder • Draw Bar • Tow Hook • Wagon Hitch   |   |



## **FACTORY FITTED OPTIONS**

- Reverse PTO
- Roll Over Protection Structure ( R
- Global front axle
- EQRL System
- Selective Control Valve (SCV) Single / Double
- Increased Lift Capacity (2500 kg)

John Deere **Genuine Parts** 

I Easily available I.





#Optional feature.


# John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.













# AYA HAI RAJA!

Ab naye avtaar mein

New PowerTech











Longer Service Interval (500 hrs.)



Factory Fitted 2nd SCV (Dual SCV)



Radiator Screen



**Combination Switch** 





J<u>DLInk</u>™



**EQRL** with Go Home Feature



Increased Fuel Tank Capacity (71 Litres)



Digital Instrument Cluster



LED Headlamp with Wrap Around Chrome Bezel





**TORQUE** 

CAPACITY - 2500 KGF