TECHNICAL SPECIFICATION

	2WD	4WD
	John Deere 3029H, 2100 EPRM, 57 HP, 3 cylinder, Turbo charged HPCR fuel injection system	
	Dry type, dual element	
Clutch	Dual	
Gear Box	12 Forward + 4 Reverse speed, 12F+12R (PR speed), 9F+3R with additional creeper speed Forward - 0.35 to 32.6 kmph (Creeper), 2.8 to 32.6 kmph (12x4 GearPRO), 1.4 to 31.3 kmph (PR Reverse - 0.61 to 20 kmph (Creeper), 3.5 to 20 kmph (12x4 GearPRO), 1.6 to 20 kmph (PR)	
Speeds		
	Hydraulic oil immersed disk brakes	
Maximum Lifting Capacity	2000 kgf (2500 kgf optional)	
3 Point Linkage	Category II, Automatic depth & draft control (ADDC)	
	Power Steering , Tilt steering *: tiltable up to 25° with lock latch	
Туре	Independent , 6 splines	
RPM	Standard : 540 @ 2100 ERPM Economy : 540 @ 1600 ERPM Reverse : 516 @2100 RPM	
PACITY	71	L
Front	7.5X16 (0.19 x 0.41 m), 8 PR 6.5 x 20 (0.17 x 0.51 m), 8 PR	9.5 x 24 (0.24 x 0.61 m), 8 PR
Rear	16.9 x 30 (0.43 x 0.76 m), 12 PR	16.9 x 30 (0.43 x 0.76 m), 12 PR
TEM	85 Ah, 12 V Battery, Cold charging Amp - 800 CCA, 60 Amp, Alternator12V, 2,5 Kv Starter Motor	
Total Weight	2320 kg	2600 kg
Wheel Base	2050 mm	2050 mm
		3678 mm
		2243 mm
		0425 mm
Turning Radius with Brakes	3181 mm	3181 mm
ORIES	• Ballast Weight • Canopy • Canopy Holder • Draw Bar • Tow Hook • Wagon Hitch	
	Maximum Lifting Capacity 3 Point Linkage Type RPM ACITY Front Rear Tetal Weight Wheel Base Overall Length Overall Length Coverall Width Ground Clearance Turning Radius with Brakes	John Deere 3029H, 2100 EPRM, HPCR fuel injection of the process of

PowerTech

FACTORY FITTED OPTIONS

- Reverse PTO
- Roll Over Protection Structure (ROPS)
- Global front axle
- EQRL System • Selective Control Valve (SCV) - Single / Double
- LED Head Lamp
- Increased Lift Capacity (2500 kg)
- Tilt Steering

High back up torque

John Deere **Genuine Parts**

I Economical I Reliable I Easily available I



#Optional feature.

John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in For more information, please contact our authorised dealer or nearest area office.







• Tractors • Implements Harvesters
 Finance





Job No: 5310 4WD GearPRO Trem IV 4pg Brochure		Language: English
Key No: 2303024262	Size: A4	Date: 13-03-2023
TU: NA	A/D: D	Image Purchased: NA

lease note: Improvement in the product is a continuous process. Hence the information given in this brochure is subject to change without prior notice. Accessories shown are not the part of standard equipmen











Jolink™



Factory Fitted 2nd SCV (Dual SCV)



EQRL with Go Home Feature



Radiator Screen



Combination Switch



owrReverser"



Increased Fuel Tank Capacity (71 Litres)



Digital Instrument Cluster



LED Headlamp with Wrap Around Chrome Bezel