



More performance, More life. Less maintenance, Useful for all farming applications



Power steering



Single piece hood with lock





## **Technical Specifications**

ENGINE

Type : John Deere 3029D, 41 HP (30.8kW),

2100 RPM, 3 Cylinders,

Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

**TRANSMISSION** 

Clutch : Single / Dual

Gear box : 8 Forward + 4 Reverse, Collarshift Speeds : Forward 3.25 - 35.51 kmph

Reverse 4.27 - 15.45 kmph

BRAKES

: Oil immersed disc brakes

**HYDRAULICS** 

Maximum Lifting

capacity : 1600 kgf

3 point linkage : Category - II
Automatic depth and draft control

(ADDC)

**STEERING** 

Type : Power

**POWER TAKE OFF** 

Type :Independent, 6 Splines Standard :540 @ 2100 ERPM Standard :540 @ 1600 ERPM

(Optional, available along with standard PTO)

WHEELS AND TYRES

Front : 6.0 X 16 (0.15 X 0.41 m), 8 PR Rear

: 12.4 X 28 (0.31 X 0.71 m), 12 PR (Optional) : 13.6 X 28 (0.34 X 0.71 m), 12 PR **FUEL TANK** 

Capacity : 60 L

ELECTRICAL SYSTEM

: 88 Ah, 12 V battery, 40 Amp. alternator

12 V, 2.5 kW Starter motor

**DIMENSIONS AND WEIGHT** 

Total weight : 1760 kg
Wheel base : 1970 mm
Overall length : 3400 mm
Overall width : 1780 mm
Ground clearance : 0390 mm
Turning radius with brakes : 2900 mm

**ACCESSORIES\*** 

Ballast weights • Canopy • Canopy holder

• Draw bar • Tow hook • Wagon hitch

**FACTORY FITTED OPTIONS** 

• Jolink™ (Alerts, Monitoring and Tracking System)

Dual PTO

 Roll over protection structure (ROPS) with deluxe seat and seat belt

Adjustable front axle

Mechanical guick raise and lower (MQRL)

**FEATURES** 

• Collarshift type qear box • PTO NSS • Water separator

• Digital Hour Meter • Mobile Charging Point with Holder

• Underhood exhaust muffler • Hydraulic auxiliary pipe

• Planetary Gear with Straight Axle • Finger Guard

Note: All the options / features may not be available in a single variant.



## Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner
 Long life and less maintenance

 High torque reserve Ideal for heavy load applications

High torque across the operating speed range

Rear oiled axle with metal face seal



Dry Type Air Filter



Oil Jet for Piston Cooling



Radiator with Overflow Reservoir



Top Shaft Lubrication

## John Deere Genuine Parts

I Economical I Reliable I Easily available I



## John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in


For more information, please contact our authorised dealer or nearest area office.











• Harvesters • Finance

